



HART Portable Ball Rack Assembly Instruction

Before beginning assembly, check all pieces have been received.

- | | |
|------------------------|-------------------------|
| A. 2 x Frame | E. 16 x Plastic Washers |
| B. 8 x Horizontal Bars | F. 16 x Bolts |
| C. 4 x Castor Wheels | G. Allen Key |
| D. 4 x Silver washers | H. Spanner |





HART Portable Ball Rack Assembly Instruction

STEP 1

Attach wheel to base of frame

This step requires 1 Frame piece, 1 silver washer and 1 wheel.

- A. Place silver washer onto wheel
- B. Screw wheel into base of frame and washer if flat against the base of the frame (use spanner if required to tight wheels to frame)
- C. Repeat for each wheel






HART Portable Ball Rack Assembly Instruction

STEP 2

Attach horizontal Bar to Main Frame

This step requires 2 frame pieces, 1 horizontal bar, 2 plastic washers, 2 bolts and the allen key.

- A. Insert one bolt through the frame with the head of the bolt on the outside.
- B. Place a black plastic washer over the bolt with the curved side facing into the frame
- C. Screw the horizontal bar onto the bolt until the black washer is firmly pressed against the frame. The Allen key will be required for this step to tighten each bolt.
- D. Repeat on the second frame piece to have the bar attached to both frame pieces.





HART Portable Ball Rack Assembly Instruction

Repeat Step Two for each bar until all bars are attached to the main frame.

Once each bar is attached, fill with balls and your set up is complete!

